

Alloy Grade 'S' Shackles - AS2741-2002

Working Load Limit	Dia. bow	Dia. Pin	Inside Width	Inside Length		Width of Bow	Approx. Weight Each			
Metric	d	D	W	L	Chain Type	L	Anchor Type	B	Screw Pin	Safety Pin
Tonnes	mm	mm	mm	mm		mm		mm	kg	kg
0.33	5	6	10		–	22		15	0.02	–
0.5	6	8	12		22	29		20	0.06	0.07
0.75	8	10	13		26	31		21	0.11	0.13
1	10	11	17		32	37		26	0.15	0.17
1.5	11	13	18		37	43		29	0.21	0.25
2	13	16	21		41	48		33	0.37	0.44
3.25	16	19	27		51	61		43	0.65	0.79
4.75	19	22	32		60	72		51	1.06	1.26
6.5	22	25	37		71	84		58	1.56	1.88
8.5	25	29	43		81	95		68	2.32	2.78
9.5	29	32	46		90	108		74	3.28	3.87
12	32	35	52		100	119		83	4.51	5.26
13	35	38	57		113	133		92	5.43	6.94
17	38	41	60		124	146		98	7.89	8.79
25	44	51	73		146	178		127	13.4	14.99
35	51	57	83		171	197		146	18.85	20.65
45	57	63	95		181	222		160	26.06	29.01
55	63	70	105		203	267		184	37.86	41.05
85	76	83	127		229	330		200	58.68	62.24
120	89	95	146		267	381		241	–	110
150	102	108	165		318	432		279	–	160